

## KNC/B label plate










Single wire, cable and conduit labelling

### PRODUCT INFORMATION

High-quality, halogen-free label for simultaneous two-sided subsequent direct labelling of wires. The KNC/B label plate made of PC material has been developed for the direct and subsequent labelling of cords and cables on the front and back. No tool required.

Available in five sizes for diameters from 1.6 - 5.7 mm.

### SPECIFICATIONS

	Polycarbonate (PC)			
	-40 – 130 °C			
	V0			
	Subsequent assembly without tools			
				

Type	Order No.	Colour	RAL equiv.	Application range from - to Ø mm (C)	Label size mm (B x A)	Printable area mm	No. characters/lines	No. per Frame	Base plate	Software Type	MOQ qty.
<b>For cable diameters of 1.6 mm to 2.0 mm</b>											
KNC/B 4,0/15-1,0	86382002	White	9016	1.50 – 2.00	4.00 x 15.00	4.00 x 15.00	8 / 1	21	GP3C-B	C24	273
KNC/B 4,0/23-1,0	86382006	White	9016	1.50 – 2.00	4.00 x 23.00	4.00 x 23.00	12 / 1	21	GP3C-B	C25	273
<b>For cable diameters of 2.0 mm to 2.5 mm</b>											
KNC/B 4,0/15-2,0	86382012	White	9016	2.00 – 2.80	4.00 x 15.00	4.00 x 15.00	8 / 1	21	GP3C-B	C26	273
KNC/B 4,0/23-2,0	86382016	White	9016	2.00 – 2.80	4.00 x 23.00	4.00 x 23.00	12 / 1	21	GP3C-B	C27	273
<b>For cable diameters of 2.9 mm to 3.6 mm</b>											
KNC/B 5,5/15-3,0	86382022	White	9016	2.80 – 3.70	5.50 x 15.00	5.50 x 15.00	8 / 1	18	GP3C-B	C28	234
KNC/B 5,5/23-3,0	86382026	White	9016	2.80 – 3.70	5.50 x 23.00	5.50 x 23.00	12 / 1	18	GP3C-B	C29	234
<b>For cable diameters of 4.1 mm to 4.6 mm</b>											
KNC/B 5,5/23-4,0	86382036	White	9016	3.80 – 4.80	5.50 x 23.00	5.50 x 23.00	12 / 1	18	GP3C-B	C30	234
<b>For cable diameters of 5.7 mm</b>											
KNC/B 7,2/23-5,0	86382046	White	9016	5.00 – 6.50	7.20 x 23.00	7.20 x 23.00	12 / 2	15	GP3C-B	C31	165

### MATERIAL PROPERTIES

 Polycarbonate (PC)

## KNC/B label plate

### THERMAL PROPERTIES



**Temperature / temperature range**  
-40 – 130 °C

### FIRE PROPERTIES



**Fire classification**  
V0

### TECHNICAL INFORMATION



**Halogen-free**  
DIN/VDE 0472, Part 815

### GENERAL TECHNICAL DATA



Subsequent assembly without tools

### ASSEMBLY METHOD



**Clamping system**

### LABELLING TECHNOLOGY



**Plotter**



**Laser devices**



**Inkjet**

All details given in our sales brochures and catalogues, as well as the information available online, are based on our current knowledge of the products described.

The electronic data and files made available by Murrplastik, particularly CAD files are based on our current knowledge of the product described.

A legally binding assurance of certain properties or the suitability for a certain purpose can not be determined from this information.

All information with respect to the chemical and physical properties of Murrplastik products, as well as application advice given verbally, in writing or by tests, is given to the best of our knowledge.

They do not release the buyer from the obligation to carry out his own tests and trials in order to determine the concrete suitability of the products for the intended purpose.

Murrplastik accepts no responsibility for the available information being up-to-date, correct or complete. Neither do we accept responsibility for the quality of this information.

Murrplastik accepts no liability for damage caused as a result of using our products.

Murrplastik reserves the right to make technical changes and improvements through constant further development of products and services.

Our General Terms and Conditions apply.

© Murrplastik Systemtechnik GmbH • proID\_135865~20200514~890286~acs\_mod\_kncb